

This listing of claims will replace all prior versions, and listings, of claims in the application.

LISTING OF CLAIMS

1. (Currently Amended) A reconfigurable speaker system for producing sound in response to at least one of a right channel audio signal and a left channel audio signals generated by an audio source, comprising:

a first audio driver operable to produce sound in response ~~[[r]]~~ to at least one of said right channel audio signal and said left channel audio signals;

a pair of second audio drivers each operable to produce sound in response to at least one of said right channel audio signal and said left channel audio signals;

a first audio signal input adapted to receive one of said right channel audio signal and said left channel audio ~~inputs~~ signal, said first ~~channel~~ audio signal input being coupled to said first audio driver and further being configured to be selectively coupled to one or both of said pair of second audio drivers; and

a second audio signal input adapted to receive the other of said right channel audio signal and said left channel audio inputs, said second audio signal input being coupled to said first audio driver and further being configured to be selectively coupled to one or both of said pair of second audio drivers.

2. (Original) The speaker system of claim 1 further comprising a switch device in circuit with said first and second audio signal inputs and said first and second audio drivers.

3. (Original) The speaker of claim 2 wherein said switch device is selectively positionable in first and second positions.

4. (Original) The speaker of claim 3 wherein in said first position of said switch device, said first audio driver is configured to produce sound in response to both of said right and left channel audio signals, and each of said pair of second audio drivers is configured to produce sound in response to a respective one of said right and left channel audio signals, and further wherein in said second position of said switch device, said first audio driver is configured to produce sound in response to only one of said right and left channel audio signals, and both of said pair of second audio drivers are configured to produce sound in response to said only one of said right and left channel audio signals.

5. (Original) The speaker system of claim 1 wherein said first audio driver comprises a dual voice coil audio driver.

6. (Original) The speaker of claim 5 wherein said first audio driver comprises a woofer.

7. (Original) The speaker system of claim 1 wherein each of said second audio drivers comprises a single voice coil audio driver.

8. (Original) The speaker of claim 7 wherein each of said second audio drivers comprises a tweeter.

9. (Original) The speaker system of claim 1 wherein each of said first and second audio signal inputs comprises a pair of electrical terminals.

10. (Original) The speaker system of claim 9 wherein said switch device comprises a double pole, single throw mechanical switch.

11. (Currently Amended) A reconfigurable speaker system for producing sound in response to at least one of right and left channel audio signals generated by an audio source, comprising:

a first audio driver operable to produce sound in response [[S]] to at least one of said right and left channel audio signals;

a pair of second audio drivers each operable to produce sound in response to at least one of said right and left channel audio signals; and

a switch device in circuit with said first and second audio [[10]] drivers and being selectively positionable in first and second positions,

wherein in said first position of said switch device, said first audio driver is configured to produce sound in response to both of said right and left channel audio signals, and each of said pair of second audio drivers is configured to produce sound in response to a respective one of said right and left channel audio signals,

and further wherein in said second position of said switch device, said first audio driver is configured to produce sound in response to only one of said right and left channel audio signals, and both of said pair of second audio drivers are configured to produce sound in response to said only one of said right and left channel audio signals.

12. (Original) The speaker system of claim 11 wherein said first audio driver comprises a dual voice coil audio driver.

13. (Original) The speaker of claim 12 wherein said first audio driver comprises a woofer.

14. (Original) The speaker system of claim 11 wherein each of said second audio drivers comprises a single voice coil audio driver.

15. (Original) The speaker of claim 14 wherein each of said second audio drivers comprises a tweeter.

16. (Original) The speaker system of claim 11 wherein said switch device comprises a double pole, single throw mechanical switch.

17. (Currently Amended) A reconfigurable speaker system for producing sound in response to at least one of right and left channel audio signals generated by an audio source, comprising:

a first audio signal input adapted to receive one of said [[5]] right and left channel audio signals;

a second audio signal input adapted to receive the other of said right and left channel audio signals;

a first audio driver coupled to both of said first and second audio signal inputs and operable to produce sound in response to at least one of said right and left channel audio signals;

a pair of second audio drivers each coupled respectively to at least one of said first and second audio signal inputs and operable to produce sound in response to at least one of said right and left channel audio signals; and

a switch device in circuit with said first and second audio signal inputs and said first and second audio drivers, and being selectively positionable in first and second positions,

wherein in said first position of said switch device, said first audio driver is configured to produce sound in response to both of said right and left channel audio signals, and each of said pair of second audio drivers is configured to produce sound in response to a respective one of said right and left channel audio signals,

and further wherein in said second position of said switch device, said first audio driver is configured to produce sound in response to only one of said right and left channel audio signals, and both of said pair of second audio drivers are configured to produce sound in response to said only one of said right and left channel audio signals.

18. (Original) The speaker system of claim 17 wherein said first audio driver comprises a dual voice coil audio driver.

19. (Original) The speaker of claim 18 wherein said first audio driver comprises a woofer.

20. (Original) The speaker system of claim 17 wherein each of said second audio drivers comprises a single voice coil audio driver.

21. (Original) The speaker of claim 20 wherein each of said second audio drivers comprises a tweeter.

22. (Original) The speaker system of claim 17 wherein each of said first and second audio signal inputs comprises a pair of electrical terminals.

23. (Original) The speaker system of claim 22 wherein said switch device comprises a double pole, single throw mechanical switch.

24. (Currently Amended) A reconfigurable speaker system for producing sound in response to at least one of right and left channel audio signals generated by an audio source, comprising:

a first speaker circuit including a woofer and a first tweeter [[5]] coupled in circuit;

a second speaker circuit including said woofer and a second tweeter coupled in circuit; and

a switch device in circuit with said first and second speaker circuits, and being selectively positionable in first and second positions,

wherein in said first position of said switch device, said woofer is configured to produce sound in response to both of said right and left channel audio signals, and each of said first and second tweeters is configured to produce sound in response to a respective one of said right and left channel audio signals,

and further wherein in said second position of said switch device, said woofer is configured to produce sound in response to only one of said right and left channel audio signals, and both of said first and second tweeters are configured to produce sound in response to said only one of said right and left channel audio signals.

25. (Cancelled).

26. (New) A reconfigurable speaker system comprising:

a source that produces a first signal and a second signal;

a switch having a first position and a second position, the switch receiving the first signal and the second signal;

a first audio driver connected to the switch, the first audio driver producing a first sound in response to one of the first signal and the second signal when the switch is located in the first position, and the first audio driver producing a second sound in response to a combination of the first signal and the second signal when the switch is located in the second position; and

a second audio driver that receives at least one of the first signal and the second signal, the second audio driver producing a third sound according to at least one of the first signal and the second signal.

27. (New) The reconfigurable speaker system of claim 26, wherein the first audio driver comprises a dual voice coil.

28. (New) The reconfigurable speaker system of claim 27, wherein the first audio driver comprises a woofer.

29. (New) The reconfigurable speaker system of claim 26, wherein the second audio driver comprises a tweeter.

30. (New) A reconfigurable speaker system comprising:

a source that produces a first signal and a second signal;

a switch having a first position and a second position, the switch receiving the first signal and the second signal;

a first audio driver connected to the switch, the first audio driver producing a first sound in response to one of the first signal and the second signal when the switch is located in the first position, the first audio driver producing a second sound in response to a combination of the first signal and the second signal when the switch is located in the second position; and

at least one second audio driver connected to the switch, the second audio driver producing a third sound in response to one of the first signal and the second signal when the switch is located in the first position, the at least one second audio driver producing a fourth sound in response to the combination of the first signal and the second signal when the switch is located in the second position.

31. (New) The reconfigurable speaker system of claim 30, wherein the first audio driver comprises a dual voice coil.

32. (New) The reconfigurable speaker system of claim 31, wherein the first audio driver comprises a woofer.

33. (New) The reconfigurable speaker system of claim 30, wherein the second audio driver comprises a dual voice coil.

34. (New) The reconfigurable speaker system of claim 33, wherein the second audio driver comprises a tweeter.